SHOPPING 325LBS SERIES



FEATURES

KINGPIN:

5/16" diameter rivet (for 0800 series); 7/16" diameter rivet (for 1000 and 1900 series) 3/16" diameter upper and lower race (for 0800 series); 7/32" diameter upper and lower race (for 1000 and 1900 series)

BUSHING: Nylon, steel, ball bearing, or precision bearing AXLE&NUT: 1/4" riveted (for 0800 series)

5/16" axle and lock nut (for 1000 and 1900 series)

Corrosion resistant bright zinc finish **FINISH:**

HARDENED: Yoke and washers

LEG SPACING: 1" (for 0800); 1 7/16" (for 1000 and H1950); 1 5/8" (for 1900 and H1950C)

Swivel

H1950C (Horn Only)

EXCELLENT FOR:

- Shopping carts
- Food service equipment
- Airports
- Mobile stock shelves
- **Bakery Equipment**



ENVIROTHANETM

Tread Width

Diameter



MOLDON POLYOLEFIN URETHANE

Capacity Lbs. Bearing Type

(200)



MOLDON POLYOLEFIN URETHANE

Wheel Type

(OLD STYLE BB-TG)

Overall Height

OPTIONS	٠
	ė

TLB	Top Locking Brake (swivel only)						
	(not available with 0820 series)						
A NI	A.d N (0000)						

- Axle and Nut (0800 series) Riveted Axle (1000 and 1900 series) AR
- C Seal (0800 and 1900 series)
- CD **Cross Drilled Holes**
- TG Thread Guards

FINISHES:

19?2 Chrome 19?4 Black

19?5 Yellow Chromate

Inquiries on other finishes welcome

Non-removable protective ball bearings and seal



•		D	Q.			9		
2 1/2"	7/8"	85 85 85	Nylon - -	2 1/8"	3"	Envirothane™ - -	S0823-3/8-16X3/4HW-U Y-S0823-3/8-16X3/4HW H0820 (Horn Only)	0.38 0.22 0.11
3"	7/8"	95 95 95	Nylon - -	2 3/8"	3 1/2"	Envirothane™ - -	S0833-3/8-16X3/4HW-U Y-S0833-3/8-16X3/4HW H0830 (Horn Only)	0.46 0.24 0.15
4"	1"	150 150 150	Ball - -	3 3/16"	4 13/16"	Envirothane™ - -	\$1043-1/2-13X1KW-U-BB-TG Y-\$1043-1/2-13X1KW-TLB-W H1040 (Horn Only)	1.29 0.59 0.32
4"	1 1/4"	250 250 300 325	- - Precision Ball	3 1/8"	4 7/8"	- - Moldon Poly. Urethane Envirothane™	Y-S1943C-1/2-13X1KW H1940 (Horn Only) S1943C-1/2-13X1KW-PLY-PB-TG S1943C-1/2-13X1KW-U-BB-TG	0.64 0.32 1.31 1.44
5"	1"	150 150 150	Ball - -	3 3/4"	5 13/16"	Envirothane™ - -	\$1053-1/2-13X1KW-U-BB-TG Y-\$1053-1/2-13X1KW-TLB-W H1050 (Horn Only)	1.53 0.58 0.32
5"	1 1/4"	250 300 325	- Precision Ball	3 15/16"	5 15/16"	- Moldon Poly. Urethane Envirothane™	Y-S1953C-1/2-13X1KW S1953C-1/2-13X1KW-PLY-PB-TG S1953C-1/2-13X1KW-U-BB-TG	0.80 1.66 1.86
	,	325 325	-	3 15/16"	5 1/2"	-	H1950 (Horn Only) H1950C (Horn Only)	0.38 0.71

Quality raceway seals, made exclusively by A



YOKE WITH 1/2-13X1 KEYWAY STEM

◆ Old Style Moldon Polyolefin Custom order run 2,500 pieces minimum. Call for availability

325

Hub Length Wheel Weight (lbs) Tread Width Capacity Lbs. Part Number Diameter Bearing Type 0 0 Ō 2 1/2" 1" 1/4" 7/8" Nylon 125 W-0820-U-1/4 0.15 1" 1/4" 7/8" Nylon W-0830-U-1/4 0.20 125 3" 1 1/4" 1 5/8" 5/16" W-1930-PLY-PB-TG-5/16 300 Precision 0.34 1" 1 7/16" 5/16" Ball W-1040-U-BB-TG-5/16 0.65 150 4" 5/16" 1 5/8" 300 Precision W-1940-PLY-PB-TG-5/16 0.60 1 1/4" 1 5/8" 5/16" Ball W-1940-U-BB-TG-5/16 0.73 350 1" 5/16" 150 1 7/16" Ball W-1050-U-BB-TG-5/16 0.89 5" 1 5/8" 5/16" W-1950-PLY-PB-TG-5/16 0.80 300 Precision 1 1/4" 1 5/8" 5/16" 350 Ball W-1950-U-BB-TG-5/16 1.00

0.71