



ENVIROTHANE™ HD

WHEELS

1,050-3,600 LBS



FEATURES

BEARINGS: Roller Bearing, Precision Ball Bearing, Tapered Bearing
TEMPERATURE: -45°F to 200°F
COLOURS: Grey (standard)
 Custom colours available, inquiries welcome.
DUROMETER: 80 (+/- 5) D Scale

DESCRIPTION: Envirothane™ HD wheels are used for high load capacities. Envirothane™ HD protects your floor and does not flat spot under static loads. Envirothane™ HD is non-corrosive, is excellent for abusive applications such as moist & wet environments and is resistant to most chemicals. Virtually maintenance free! Moisture friendly!

EXCELLENT FOR:

- Floor protection
- Factory use
- Moist & wet environments
- Platform & stock trucks
- Outdoor use & heavy loads
- Heavy material handling
- Smooth, easy rolling & longevity
- Towline applications
- Hotel & food service equipment
- Heavy material handling
- Abusive applications
- Ease of maneuverability
- Prolonging of equipment life



ENVIROTHANE™ HD

OPTIONS:

- A Alternative Hub
- BB Ball Bearing
- BBSS Stainless Steel Ball Bearing
- BR Bronze Bushing
- PB Precision Ball Bearing
- PBSS Stainless Steel Precision Bearing
- RBSS Stainless Steel Roller Bearing
- TG Thread Guards

SPECIAL:

- Resistant to most chemicals
- Non-marking under normal conditions
- Non-corrosive
- Moisture friendly
- Maintenance free
- One piece solid Envirothane™ HD
- Good floor protection
- Crowned tread reduces amount of friction between tread & floor

WHEEL

PART NUMBER

| Diameter | Tread Width | Capacity Lbs. | Hub Length | Standard Bore | Alternative Bore | Bearing Type | Part Number | Wheel Weight (lbs) |
|----------|-------------|---------------|------------|---------------|------------------|--------------|----------------|--------------------|
| 3" | 2" | 1,050 | 2 3/8" | 1/2" | - | Precision | W-7003-UGH-PB | 0.86 |
| 4" | 2" | 1,050 | 2 3/8" | 1/2" | - | Precision | W-7004-UGH-PB | 1.15 |
| 5" | 2" | 1,200 | 2 3/8" | 1/2" | - | Precision | W-7005-UGH-PB | 1.53 |
| 6" | 2" | 1,500 | 2 3/8" | 1/2" | - | Precision | W-7006-UGH-PB | 1.87 |
| | 2 1/2" | 2,300 | 2 3/4" | 3/4" | - | Precision | W-7106-UGH-PB | 3.55 |
| | 3" | 2,750 | 3 1/4" | 3/4" | 1" | Precision | W-7506-UGH-PBB | 3.70 |
| 8" | 2" | 1,800 | 2 3/8" | 1/2" | - | Precision | W-7008-UGH-PB | 2.98 |
| | 2 1/2" | 2,400 | 2 3/4" | 3/4" | - | Precision | W-7108-UGH-PB | 5.53 |
| | 3" | 3,000 | 3 1/4" | 3/4" | 1" | Precision | W-7508-UGH-PBB | 4.83 |
| 10" | 2 1/2" | 3,000 | 2 3/4" | 3/4" | - | Precision | W-7110-UGH-PBB | 7.41 |
| | 3" | 3,400 | 3 1/4" | 3/4" | 1" | Precision | W-7510-UGH-PBB | 6.81 |
| 12" | 3" | 3,600 | 3 1/4" | 3/4" | 1" | Precision | W-7512-UGH-PBB | 7.83 |

