



MOLDON ALUM. URETHANE

WHEELS

700-1,500 LBS



FEATURES

BEARINGS: Plain, Ball, Delrin, Nylon, Roller, Caged Roller Bearing
TEMPERATURE: -45°F to 180°F
COLOURS: Aluminum Core, Red Tread
DUROMETER: 92.5 (+/- 2.5) A Scale

DESCRIPTION: Moldon Aluminum Urethane is secured to aluminum core. This wheel allows for an easy, smooth, quiet ride. The Moldon Aluminum Urethane is excellent when looking for a wheel that will give maximum floor protection while carrying heavy loads. The tread is chemically resistant and the core is resistant to rust.

EXCELLENT FOR:

- Moist and wet environments
- Resistant to most chemicals
- Cushion ride
- Quiet and easy rolling
- Shock and vibration
- Prolonging equipment life
- Floor protection
- Rejects floor debris
- Platform trucks
- Food service and hotel equipment
- Large stock trucks
- Factory use
- Textile carts
- Abusive applications



MOLDON ALUMINUM URETHANE

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
4"	1 1/2"	700	1 5/8"	1 3/16"	5/16" * 3/8" * 5/8" * 3/4"	Plain	W-6204-MAU	0.79
		700	1 13/16"	1/2"		Roller	W-6204-MAU-RB	1.09
	2"	800	2 3/16"	1 3/16"	3/8" * 5/8" * 3/4"	Plain	W-7004-MAU	1.00
		800	2 3/8"	1/2"		Roller	W-7004-MAU-RB	1.44
5"	1 1/2"	800	1 5/8"	1 3/16"	5/16" * 3/8" * 5/8" * 3/4"	Plain	W-6205-MAU	1.14
		800	1 13/16"	1/2"		Roller	W-6205-MAU-RB	1.44
	2"	1,000	2 3/16"	1 3/16"	3/8" * 5/8" * 3/4"	Plain	W-7005-MAU	1.40
		1,000	2 3/8"	1/2"		Roller	W-7005-MAU-RB	1.84
6"	1 1/2"	900	1 5/8"	1 3/16"	5/16" * 3/8" * 5/8" * 3/4"	Plain	W-6206-MAU	1.48
		900	1 13/16"	1/2"		Roller	W-6206-MAU-RB	1.78
	2"	1,200	2 3/16"	1 3/16"	3/8" * 5/8" * 3/4"	Plain	W-7006-MAU	1.98
		1,200	2 3/8"	1/2"		Roller	W-7006-MAU-RB	2.42
8"	2"	1,500	2 3/16"	1 3/16"	3/8" * 5/8" * 3/4"	Plain	W-7008-MAU	3.04
		1,500	2 3/8"	1/2"		Roller	W-7008-MAU-RB	3.48

OPTIONS:

- BB Ball Bearing
- BR Bronze Bushing
- DB Delrin Bearing
- NB Nylon Roller Bearing
- NBSS Stainless Steel Nylon Roller Bearing
- RB Roller Bearing
- RBC Caged Roller Bearing
- RBSS Stainless Steel Roller Bearing
- SSW Steel Side Washer
- SWH Heat-treated Side Washer
- TG Thread Guard
- Z Zerk in Wheel

SPECIAL:

- NB may be substituted for RB
- Resistant to most chemicals
- Non-marking
- Moisture friendly
- Maintenance free