



PNEUMATIC

300-620LBS

WHEELS



FEATURES

BEARINGS: Sealed Precision Ball Bearings (unless otherwise specified)
TEMPERATURE: -20°F to 130°F
FINISH: Steel Grey Hub
SPECIAL: Ply rating is 4, maximum PSI is 50 (unless otherwise specified)

DESCRIPTION: Pneumatic wheels are excellent for applications where floor and equipment protection is vital. The air pressure provides for shock absorption, quiet operation and ease of rolling. Excellent for delicate materials and uneven and rough floor surfaces. For manual operation only.

EXCELLENT FOR:

- Uneven floors such as agricultural, institutional and industrial
- Quiet Cushion ride
- Shock and Vibration
- Prolonging equipment life
- Floor Protection
- Platform and Large stock trucks
- Food Service equipment
- Hotel Equipment



PNEUMATIC LUG



PNEUMATIC SAWTOOTH

HUB SIZE:

HUB LENGTH	CODE#
2"	A
2 1/4"	B
2 1/2"	C
2 3/4"	K
2 5/8"	D
3"	E
3 1/4"	I
4"	F
4 1/4"	H

WHEEL										PART NUMBER	
Diameter	Tread Width	Capacity Lbs.	Hub Length	Hub Type	Tire Colour	Standard Bore	Alternative Bore	Bearing Type	Tread Style	Part Number	Wheel Weight (lbs)
8"	2 1/2" (2.50-4)	300	2 1/4"	Center	Black	1/2"	5/8" * 3/4"	Precision Ball	Lug	W-7908-PNCB-PBB	3.00
		300	2 1/4"	Offset	Black	5/8"	1/2" * 3/4"	Precision Ball	Lug	W-7908-PNOB-PBB	3.00
		300	3"	Center	Black	1/2"	5/8" * 3/4"	Precision Ball	Lug	W-7908-PNCE-PBB	3.00
10"	3 1/2" (4.10/3.50-4)	350	2"	Center	Black	3/4"	1/2" * 5/8"	Precision Ball	Sawtooth	W-7910-PNCA-PBB	4.00
		350	2"	Offset	Black	5/8"	1/2" * 3/4"	Precision Ball	Sawtooth	W-7910-PNOA-PBB	4.00
		350	2 1/4"	Offset	Black	5/8"	1/2" * 3/4"	Precision Ball	Sawtooth	W-7910-PNOB-PBB	4.00
		350	3"	Center	Black	3/4"	1/2" * 5/8"	Precision Ball	Sawtooth	W-7910-PNCE-PBB	4.00
		350	4"	Center	Black	1/2"	5/8" * 3/4"	Precision Ball	Sawtooth	W-7910-PNCF-PBB	4.00
12"	3 1/2" (4.10/3.50-6)	450	4"	Center	Black	1/2"	5/8" * 3/4"	Precision Ball	Sawtooth	W-7912-PNCF-PBB	6.60
16"	4" (4.80/4.00-8)	575	4"	Center	Black	3/4"	1/2" * 5/8"	Precision Ball	Rib	W-7916-PNCF-PBB	11.50
	6 1/2" (16X6.50-8)	620	4"	Center	Black	1"	-	Ball	Traction	W-781665-PNCF-BBΔ	13.25

* All 8", 10" and 12" Pneumatics are fitted with a 3 pc. Split Rim / Bolt through flanged hub design

* Special Order / Designs available by special order

Δ 30 PSI max.