275-500lbs WHEELS

FEATURES

BEARINGS: Precision Ball Bearings TEMPERATURE: -20°F to 130°F COLOURS: Silver Core, Black Tread, UV Grey DUROMETER: 94 (+/- 4) A Scale

DESCRIPTION: Flat Free tires provide the bounce and load handling characteristics similar to pneumatic tires, except they never lose air. Flat Free are excellent for applications where floor and equipment is vital. The wheel provides for shock absorption, quiet operation and of rolling. Flat Free are light weight, non-marking moulded onto a heavy duty steel rim with high quality sealed ball bearings. For manual operation only.

EXCELLENT FOR:

- Uneven floors such as agricultural, . institutional and industrial
- Quiet Cushion ride
- Moist environments
- Shock and Vibration .
- Pro
- • •
- Flor Pla Foo Hot Sm Fac Tex

Anosive abblication

HUB SIZE:	
HUB LENGTH	CODE#
2"	A
2 1/4"	В
2 1/2"	C
2 5/8"	D
3"	E
3 1/4"	- I
4"	F
4 1/4"	Н











rolonging equi	ipment life (W/H										PART NUMBER	
loor Protection latform and Large stock trucks ood Service equipment lotel Equipment mall waste bins actory use extile carts busive applications		Diameter	Tread Width	Capacity Lbs.	Hub Length	Hub Type	Tire Colour	Standard Bore	Alternative Bore	Bearing Type	Tread Style	Part Number	Wheel Weight (lbs)
		6"	2"	275	2 1/2"	Center	Black	1/2"	-	Precision Ball	Sawtooth	W-7006-FFCC-PBB	1.70
		8"	2"	280	2 1/2"	Center	Black	1/2"	-	Precision Ball	Sawtooth	W-7008-FFCC-PBB	1.70
SIZE:	2 1/2'' (2.50x4)		275 275 275	2 ¹ /4" 3" 3"	Offset Center Center	Black Black Grey	5/8" 1/2" 1/2"	$\frac{1}{2}$ "* $\frac{3}{4}$ " $\frac{5}{8}$ "* $\frac{3}{4}$ " $\frac{5}{8}$ "* $\frac{3}{4}$ "	Precision Ball Precision Ball Precision Ball	Lug Lug Lug	W-7908-FF0B-PBB W-7908-FFCE-PBB W-7908-FFCEG-PBB*	2.70 2.70 2.70	
NGTH " /4" /2" /8"	CODE# A B C D	10"	3 1/2" (4.10/3.50x4)	300 300 300 300 300	2" 2 ¹ /4" 3" 4"	Offset Offset Center Center	Black Black Black Black	5/8" 5/8" 5/8" 1/2"	$\frac{1/2"*3/4"}{1/2"*3/4"}$ $\frac{1/2"*3/4"}{1/2"*3/4"}$ $\frac{5}{8"*3/4"}$	Precision Ball Precision Ball Precision Ball Precision Ball	Sawtooth Sawtooth Sawtooth Sawtooth	W-7910-FFOA-PBB W-7910-FFOB-PBB W-7910-FFCE-PBB W-7910-FFCF-PBB	3.75 3.75 3.75 4.00
/4"	E	12"	3 1/2'' (4.10/3.50x6)	400	4"	Center	Black	1/2"	5/8 "* 3/4"	Precision Ball	Sawtooth	W-7912-FFCF-PBB	6.00
/4"	F H	16"	4'' (4.80/4.00x8)	500	4"	Center	Black	3/4"	1/2 "* 5/8"	Precision Ball	Rib	W-7916-FFCF-PBB	8.00

* Special Order / Designs available by special order

SPECIAL:

Non-marking under normal conditions Light weight Less downtime Maintenance Free Moisture friendly Many combinations of core and tread colours available Sealed Ball Bearing