WHEELS

325-1,400 LBS



FEATURES

BEARINGS: Plain, Ball, Precision, Roller Bearing, Caged Roller Bearing

TEMPERATURE: -20°F to 290°F continuously

COLOURS: White

DESCRIPTION: This non-marking wheel features an exclusively developed proprietary polypropylene material which is excellent for high load capacities.

The Retort wheel is extremely ergonomically efficient, as it requires minimum effort to roll and swivel with heavy loads. Retort wheel resists hard impacts and is resistant to most chemicals, solvents, gases, acids, steam cleaning and does not absorb water! This wheel is ideal for industrial and institutional applications.

DUROMETER: 75 D Scale

EXCELLENT FOR:

- Floor protection
- Factory use
- Push/Pull Ease
- Food processing
- Platform and Stock trucks
- Heavy material handling
- Smooth, easy rolling
- Abusive applications
- Bakery applications
- Pharmaceutical applications
- Wash-Station applications
- Prolonging of equipment life

OPTIONS:

Ball Bearing

Heat-treated Ball Bearing **BBHT**

(2" wheel tread)

BR **Bronze Bushing**

RB **Roller Bearing**

RBC Caged Roller Bearing RBSS

Stainless Steel Roller Bearing **SWH** Heat-treated Side Washer

Through Bore (2" wheel tread)

SPECIAL:

Resistant to most chemicals Non-marking Debris rejecting tread Moisture Friendly Maintenance free One piece solid Retort



RETORT

WHEEL PART NUMBER								
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
3"	1 1/4"	325 325	1 ⁹ /16" 1 ⁹ /16"	1/2" 5/16"	- 3/ ₈ "	Plain Steel	W-1930-RET W-1930-RET	0.25 0.30
	1 1/2"	340 340 340	1 ⁵ /8" 1 ⁵ /8" 1 ¹³ /16"	3/8" 1 3/16" 1/2"	5/16" 1/2"* 5/8" 3/8"* 5/8"* 3/4"	Steel Plain Roller	W-6203-RET W-6203-RET W-6203-RET-RB	0.35 0.30 0.60
4"	1 1/4"	350 350] ⁹ /16"] ⁹ /16"	1/2" 5/16"	- 3/ ₈ "	Plain Steel	W-1940-RET W-1940-RET	0.38 0.42
	1 1/2"	500 500 500	1 ⁵ /8" 1 ⁵ /8" 1 ¹³ /16"	3/8" 1 3/16" 1/2"	5/16" 1/2"* 5/8" 3/8"* 5/8"* 3/4"	Steel Plain Roller	W-6204-RET W-6204-RET W-6204-RET-RB	0.50 0.45 0.75
	2"	500 500	2 ³ /16" 2 ³ /8"	1 ³ /16" 1/2"	- 5/8"* 3/4"	Plain Roller	W-7004-RETW [◆] W-7004-RETW-RB	0.77 1.21
5"	1 1/4"	450 450] ⁹ /16"] ⁹ /16"	1/2" 5/16"	- 3/ ₈ "	Plain Steel	W-1950-RET W-1950-RET	0.54 0.58
	1 1/2"	550 550 550	1 ⁵ /8" 1 ⁵ /8" 1 ¹³ /16"	3/8" 1 3/16" 1/2"	5/16" 1/2"* 5/8" 3/8"* 5/8"* 3/4"	Steel Plain Roller	W-6205-RET W-6205-RET W-6205-RET-RB	0.63 0.58 0.88
	2"	650 650	2 ³ /16" 2 ³ /8"	1 ³ /16" 1/2"	- 5/8"* 3/4"	Plain Roller	W-7005-RETW* W-7005-RETW-RB	1.20 1.64
6"	2"	700 700	2 ³ /16" 2 ³ /8"	1 ³ /16"	- 5/8"* 3/4"	Plain Roller	W-7006-RETW* W-7006-RETW-RB	1.44 1.88
8"	2"	900 900	2 ³ /16" 2 ³ /8"	1 ³ /16"	- 5/8"* 3/4"	Plain Roller	W-7008-RETW* W-7008-RETW-RB	2.50 2.94
	2 1/2"	1,400 1,400	2 ³ / ₄ " 2 ²⁷ / _{3 2} "	1 15/1 6" 3/4"	-]"*] ¹ /4"	Plain Roller	W-7108-RET W-7108-RET-RB	3.90 2.04



wheel has one closed side to eliminate side washer and for easier assembly