



ICE™ WHEELS

80-100LBS



FEATURES

BEARINGS: Precision ball bearing
TEMPERATURE: -45°F to 180°F
COLOURS: Clear, Blue, Black, Green, Orange, Purple, Pink, Red
DUROMETER: 55 (+/-5) D Scale

DESCRIPTION: This solid non-marking polyurethane wheel is securely bonded mechanically to its polyolefin core to prevent separation. Top quality wheel provides for good floor protection and will not flat spot under standing loads. Excellent rollability under load provided by precision ball bearings. It is resistant to chemicals and excellent for all floor surfaces.

EXCELLENT FOR:

- Economical
- Display racks
- Good Floor Protection
- Resistant to most chemicals
- Cushion ride
- Prolonging equipment life
- Easy rollability under load



ICE CLEAR
(ICE)



ICE BLUE
(ICEB)



ICE BLACK
(ICEBL)



ICE GREEN
(ICEG)



ICE ORANGE
(ICEO)



ICE PURPLE
(ICEP)



ICE PINK
(ICEPI)



ICE RED
(ICER)

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
2"	7/8"	80	1 3/64"	1/4"	-	Precision	W-0800-ICE-PB	0.16
		80	1 3/64"	1/4"	-	Precision	W-0800-ICEB-PB	0.16
		80	1 3/64"	1/4"	-	Precision	W-0800-ICEBL-PB	0.16
		80	1 3/64"	1/4"	-	Precision	W-0800-ICEG-PB♦	0.16
		80	1 3/64"	1/4"	-	Precision	W-0800-ICER-PB	0.16
2 5/16"	3/4"	80	1 3/64"	1/4"	-	Precision	W-0820-ICE-PB	0.16
		80	1 3/64"	1/4"	-	Precision	W-0820-ICEB-PB	0.16
		80	1 3/64"	1/4"	-	Precision	W-0820-ICEG-PB	0.16
		80	1 3/64"	1/4"	-	Precision	W-0820-ICER-PB♦	0.16
3"	15/16"	100	1 3/64"	1/4"	-	Precision	W-0830-ICE-PB	0.25
		100	1 3/64"	1/4"	-	Precision	W-0830-ICEB-PB	0.25
		100	1 3/64"	1/4"	-	Precision	W-0830-ICEG-PB	0.25
		100	1 3/64"	1/4"	-	Precision	W-0830-ICEO-PB♦	0.25
		100	1 3/64"	1/4"	-	Precision	W-0830-ICEP-PB♦	0.25
		100	1 3/64"	1/4"	-	Precision	W-0830-ICEPI-PB	0.25
		100	1 3/64"	1/4"	-	Precision	W-0830-ICER-PB	0.25

SPECIAL:

- Smooth rolling
- Non-marking
- Quiet & easy rolling
- Long life tread
- Ball bearings
- Custom colours available upon request

♦ Custom order run 2,500 pieces minimum. Call for availability