



# **FEATURES**

**BEARINGS:** Plain, Stainless Steel Ball, Delrin, Stainless Steel Precision

Ball, Stainless Steel Roller

TEMPERATURE: 250°F (max for load rating)

Up to 800°F (please contact office for details)

COLOURS: Steel Grey

HARDNESS: Brinell 123

DESCRIPTION: 304 wheels are toughened for strength and longevity.

While the 304 wheel is always competitive for its weight, it is mainly used for rugged and concrete floors. This wheel could cause floor wear and it is rather noisy.

### **EXCELLENT FOR:**

- Bacteria-free environments
- Corrosive environments
- Factory use
- Food processing
- Chemical plants
- Pharmaceutical
- Platform trucks
- Autoclaves
- **Animal Cages**
- Heavy material handling
- Easy rolling Heavy loads
- Moisture friendly environments



**304 STAINLESS** 

V GROOVE 304

## **OPTIONS:**

BBSS Stainless Steel Ball Bearing DB

Delrin Bearing Stainless Steel Precision Ball Bearing PBSS RB Stainless Steel Roller Bearing (only)

Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
3"	1 1/2"	600 600	] <sup>5</sup> /8" ] <sup>13</sup> /16"	1 <sup>3</sup> /16"	5/16"* 3/8"* 1/2"* 3/4"	Plain Roller	W-6203-304 W-6203-304-RB	2.64 3.10
		600 600	] <sup>5</sup> /8" ] <sup>13</sup> /16"	1 <sup>3</sup> /16"	5/16"* 3/8"* 1/2"* 3/4"	Plain Roller	W-6203-VG304 W-6203-VG304-RB	2.11 2.57
4"	1 1/2"	600 600	] <sup>5</sup> /8" ] <sup>13</sup> /16"	1 <sup>3</sup> /16"	5/16"* 3/8"* 1/2"* 3/4"	Plain Roller	W-6204-304 W-6204-304-RB	5.03 5.49
		600 600	] <sup>5</sup> /8" ] <sup>13</sup> /16"	1 <sup>3</sup> /16"	5/16"* 3/8"* 1/2"* 3/4"	Plain Roller	W-6204-VG304 W-6204-VG304-RB	4.28 4.74
	2"	850 850	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16"	1/2"* 3/4" 3/4"	Plain Roller	W-7004-304 W-7004-304-RB	6.71 7.24
		850 850	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16"	1/2"* 3/4" 3/4"	Plain Roller	W-7004-VG304 W-7004-VG304-RB	5.96 6.49
5"	2"	950 950	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16"	1/2"* 3/4" 3/4"	Plain Roller	W-7005-304 W-7005-304-RB	10.79 11.32
		950 950	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16"	1/2"* 3/4" 3/4"	Plain Roller	W-7005-VG304 W-7005-VG304-RB	9.85 10.38
6"	2"	1,200 1,200	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16"  1/2"	1/2"* 3/4" 3/4"	Plain Roller	W-7006-304 W-7006-304-RB	15.77 16.30
		1,200 1,200	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16"	1/2"* 3/4" 3/4"	Plain Roller	W-7006-VG304 W-7006-VG304-RB	14.79 15.32
	3"	3,500 3,500	3 1/4" 3 7/16"	1 <sup>15</sup> /16" 3/4"	- ]"* ] <sup>1</sup> /4"	Plain Roller	W-9106-304 W-9106-304-RB	22.22 24.21
		3,500 3,500	3 1/4" 3 7/16"	1 <sup>15</sup> /16" 3/4"	- ]"* ] <sup>1</sup> /4"	Plain Roller	W-9106-VG304 W-9106-VG304-RB	21.18 23.17







WHEELS

WHEEL PART NUMBER										
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)		
8"	2"	1,500 1,500	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16" 1/2"	1/2"* 3/4" 3/4"	Plain Roller	W-7008-304 W-7008-304-RB	28.47 29.00		
		1,500 1,500	2 <sup>3</sup> /1 6" 2 <sup>3</sup> /8"	1 <sup>3</sup> /16"	1/2"* 3/4" 3/4"	Plain Roller	W-7008-VG304 W-7008-VG304-RB	26.96 27.49		
	3"	3,500 3,500	3 <sup>1</sup> /4" 3 <sup>7</sup> /16"	1 <sup>15</sup> /16" 3/4"	3/4"* 1"* 1 1/4" 1"* 1 1/4"	Plain Roller	W-9108-304 W-9108-304-RB	41.28 43.27		
		3,500 3,500	3 1/4" 3 <sup>7</sup> /16"	1 15/16" 3/4"	3/4"* 1"* 1 1/4" 1"* 1 1/4"	Plain Roller	W-9108-VG304 W-9108-VG304-RB	41.28 43.27		
10"	3"	3,500 3,500	3 1/4" 3 <sup>7</sup> /16"	1 <sup>15</sup> /16" 3/4"	3/4"* 1"* 1 1/4" 1"* 1 1/4"	Plain Roller	W-9110-304 W-9110-304-RB	65.80 67.79		
		3,500 3,500	3 1/4" 3 7/16"	1 15/16" 3/4"	3/4"* 1"* 1 1/4" 1"* 1 1/4"	Plain Roller	W-9110-VG304 W-9110-VG304-RB	64.03 66.02		
12"	3"	3,500 3,500	3 1/4" 3 7/16"	1 15/16" 3/4"	3/4"* 1"* 1 1/4" 1"* 1 1/4"	Plain Roller	W-9112-304 W-9112-304-RB	95.76 97.76		

\* Custom sizes available