



GL33™

LOW PROFILE SERIES

1,000 LBS



FEATURES

KINGPIN: 5/8" diameter heavy duty kingpin
RACEWAY: 1/4" diameter upper race; 1/4" diameter lower race (equal diameter raceway)
BUSHING: Roller bearing

AXLE&NUT: 1/2" heat treated axle and lock nut
FINISH: Corrosion resistant bright zinc
HARDENED: Yoke & Washer
LEG SPACING: 2 5/16"

EXCELLENT FOR:

- Appliances
- Store fixtures
- Computer equipment
- Metal equipment
- Business machines
- Food equipment
- Freezers
- Abusive application
- Floor protection & excellent mobility



ROLLX™

WHEEL		CASTER				PART NUMBER				
Diameter	Tread Width	Capacity Lbs.	Bearing Type	Swivel Radius	Overall Height	Wheel Type	Swivel	Caster Weight (lbs)	Rigid	Caster Weight (lbs)
3"	1 3/4"	1,000	Roller	2 5/16"	4 1/32"	RollX™-WOW	SGL33-E17F-RXW-RB	1.06	Not Available	-

OPTIONS:

TSB Thumb Screw Brake

FINISHES:

- 4F Black Flat
- 4G Black Gloss
- 4I Black Ionic
- 2 Chrome

Inquiries on other finishes welcome

PLATE DIAGRAMS

STANDARD SWIVEL PLATE: E17F

F - Plate Thickness: 5/32"

